3nh.com

www.3nh.com

One-key to measure density CMYK & color LAB value



YD5010Plus-Spectrodensitometer

Under the 45/0 geometric optical illumination and the testing conditions of M O, M 1, M 2 , M 3 stipulated by ISO 13655 standard, the instrument can accurately measure the reflectance data of samples. Under multiple color spaces, it can accurately measure various printing density indexes, color difference formulas and color indexes, and can meet the user's regular testing of various parameters.



Con-cave Grating

LED light

High hardware configuration

USB interface

ISO 9001 Certified

© 2019 All rights reserved.

PRODUCT FEATURES

1.Perfect combination of the beautiful appearance and the ergonomic structure design.
1.Combined LED light sources with long life and low power consumption, including UV light.
2.Switchable apertures: Φ2/4/8mm, adapt to more samples.
4.Accurately measure reflectance spectrum, CMYK density and Lab value of the sample.
5.High-configuration electronic hardware: 3.5-inch TFT true-color screen, capacitive touch screen, concave grating, 256-pixel dual-array CMOS image sensor, etc..
6.Two standard observer angles: 2/10, multiple light source modes and color systems.
7.USB mode can extend more function.
8.Large-capacity storage space, over 10,000 test data.
9.Especially suitable for process control and quality control of printing factory.
10.PC software has powerful function expansion.
11.Optional accessories: Micro printer, without computer can continuously print out the measurement of various parameters, easy to save.





APPLICATION INDUSTRY

It is widely used in ink, printing, film processing, textile dyeing, plastic electronics and other industries for accurate color measurement and quality control, as well as in scientific research institutions, quality testing institutions, laboratories; especially suitable for precise measurement and quality control of optical density and dot enlargement in ink printing.


Ink & Printing


Paper


Textile


Automobile


Plastics


Laboratory

Other

SPECIFICATION PARAMETER

Model: YD5010Plus
Illumination: 45/0(45 circular illumination, vertical viewing)
Standard: ISO 5-4, CIE No.15
Light Source: Combined LED source, UV light
Spectral mode: Concave-Grating
Sensor: 256-pixel dual-array CMOS image sensor
Wavelength range: 400~700nm
Wavelength pitch: 10nm
Half bandwith: 10nm
Measurement conditions: meet the ISO 13655 measurement conditions: M0 (CIE light source A); M1 (CIE light source D50) M2 (excluding UV illumination); M3 (M2 + polarized light filter)
Density standard: ISO Status T、E、A、I
Density index: density value, density difference, dot area, dot increase, overprint, printing characteristics, printing contrast, tone error and grayscale
Measurement Aperture: Φ2mm、Φ4mm、Φ8mm
Color Space: CIE L AB,XYZ,Yxy,LCh
Color difference formula: ΔE*ab, △E*94 △E*00
Other colorimetric indexes: WI(ASTM E313, CIE/ISO,AATCC,Hunter), YI(ASTM D1925, ASTM 313), MI, Cover Ratio
Observer Angle : 2°/10°
Illuminant: D65,A,C,D50,D55,D75,F2(CWF),F7(DLF),F11,F12
Measuring time: Approx. 1.5s
Repeatability: density value：within 0.01D
Chromaticity value: within ΔE*ab 0.04
Inter-instrument agreement: within ΔE*ab 0.2（Average for 14 BCRA series II color tiles,except -M3）
Measurement method: single measurement, average measurement (2-99 times)
Size: L*W*H: 184X77X105mm
Weight: Approx. 600g
Battery life: lithium battery, 5000 times of using after charging for 8 hours
Lighting source life: 5 years, more than 3 million measurements
Display screen: TFT true color 3.5 inch,
Touch Screen Interface: USB
Storage: 10,000
Language: simplified Chinese, English, Traditional Chinese
Standard accessories: power adapter, data line, built-in lithium batteries, instructions, quality control software (+download from official website), black and white calibration board, protection cover, polarization filter box
Optional accessories: Micro printer

GUANGDONG THREENH TECHNOLOGY CO., LTD.


Spectrophotometers


Colorimeters


Haze Meters


Gloss Meters


Test Charts


Light Booths

★CONTACT US

web:www.3nh.com
Email:3nh@3nh.com
Tel:0086-020-82880288
Add: 6-8th floors, Building B33, Low Carbon Headquarters Park, Xincheng Road No.400, Zengcheng District, Guangzhou, Guangdong Province, China

The specifications and design may be changed without notice.