

One key to complete intelligent color measurement



7 inches TFT Capacitive Touch-screen



USB/Bluetooth



Wavelength range
360nm – 780nm



Built-in camera
locating



ISO 9001
Certified



YS6060 Benchtop Grating Spectrophotometer

YS6060 is a benchtop grating spectrophotometer which is developed by our independently with proprietary intellectual property. YS6060 has many features, like 7 inches TFT capacitive touch screen display, full illuminants, reflective d/8 and transmissive d/0 geometry(including or excluding UV). With very stable and precise color measurement, large storage and powerful PC software all makes YS6060 ideal for color analysis within R&D and laboratory environments.

APPLICATION INDUSTRY

YS6060 benchtop spectrophotometer is designed for accurate analysis and transmission of laboratory color and appearance of solids, liquids, pastes, powders, pills, and granules in a more comprehensive, streamlined process. YS6060 is widely used in paints, inks, textiles, garments, printing and dyeing, printing etc industries for color transfer and quality control.



Automobile



Leather



Plastics




Paint



Food stuff



Laboratory



Others

PRODUCT FEATURES

- 1.High configuration of hardware: 7 inches TFT Color Capacitive Touch–screen Display; Concave Grating.
- 2.Double Array 256 Image Element CMOS Sensor; Long life–span stable LED, UV LED and xenon lamp.
- 3.With reflective and transmissive spectrum, accurate Lab value, good to calculate color formula and do precise color transmission.
- 4.Auto identify measuring aperture. Freely switchable between 4 measuring apertures: ϕ 25.4mm/8mm/4mm. Users also can customize apertures.
- 5.Built–in temperature sensor to monitor and compensate the measuring temperature to ensure the measurement more precision.
- 6.Wavelength range 360nm – 780nm. Built–in 400nm cut off/460nm cut off (only xenon lamp edition), more professional in UV measurement.
- 7.Independent light source detector, continuously monitor the condition of light sources to ensure the light source reliable.
- 8.Multiple measurement modes: Quality Management Mode, Sample Mode; Meet more users' requirement.
- 9.Multiple accessories, sample holders, fixation clamp, suitable to more working condition.
- 10.Big capacity data storage, for 20000 pieces test result.
- 11.Built–in camera locating.
- 12.More powerful extended functions at the PC software.



PRODUCT HIGHLIGHTS



Plastic Sample

Auto–identify the apertures, 25.4/8/4mm three apertures freely switch. Special aperture can be customised.



Transmissive Sample

Transmittance Measurement: Adopt $D/0^\circ$ Geometry, conform to ISO, CIE, ASTM and DIN standard.



Liquid, Powder, Solid Sample Measurement



Measuring Apertures

Auto–identify the apertures, 25.4/15/8/4mm three apertures freely switch. Special aperture can be customised.

OPTIONAL ACCESSORIES

The instrument is equipped with a variety of optional accessories: Micro printer, instrument inverted test fixture, petri dish, Meet customer multi-sample measurement.



Microprinter



Instrument upside down test fixture



Petri dish

YS6060 Specification

Optical Geometry: Reflectance: d/8 (SCI&SCE; Include UV/Exclude UV) Transmittance: d/0 (SCI&SCE; Include UV/Exclude UV)

Comply to standard: CIE No.15, GB/T 3978, GB 2893, GB/T 18833, ISO7724/1, ASTM E1164, DIN5033 Teil7

Integrating Sphere Size: Φ 154mm

Light Source Device: 360nm-780nm Combined LED Lamp, 400nm cut-off, 420nm cut-off, UV Lamp

Sensor: 256 Image Element Double Array CMOS Image Sensor

Light Source Device: 360nm-780nm Combined LED Lamp, 400nm cut-off, 420nm cut-off, UV Lamp

Wavelength Pitch: 10nm

Semiband Width: 5nm

Reflectance Range: 0~200%

Measuring Aperture: Reflective: Φ 30mm/ Φ 25.4mm, Φ 18mm/ Φ 15mm, Φ 10mm/ Φ 8mm, Φ 6mm/ Φ 4mm; Transmissive: Φ 30mm/ Φ 25.4mm

Specular Component: Reflectance: SCI&SCE Transmittance: SCI&SCE

Color Space: CIE LAB, XYZ, Yxy, LCh, CIE LUV, Musell, s-RGB, HunterLab, β xy, DIN

Color Difference Formula: ΔE_{ab} , ΔE_{uv} , ΔE_{94} , $\Delta E_{cmc}(2:1)$, $\Delta E_{cmc}(1:1)$, ΔE_{00} , DIN ΔE_{99} , ΔE (Hunter)

Colorimetric Index: WI (ASTM E313, CIE/ISO, AATCC, Hunter), YI (ASTM D1925, ASTM 313), MI (Metamerism Index), Staining Fastness,

Color Fastness, Color Strength, Opacity, Gardner Index, APHA/Hazen/Pt-Co Index, 555 Index, Saybolt, ASTM D1500 color code, Haze (ASTM D1003)

Observer Angle: 2° & 10°

Illuminants: D65A, C, D50, D55, D75, F1, F2, F3, F4, F5, F6, F7, F8, F9, F10, F11, F12, CWF, DLF, TL83, TL84, TPL5, U30

Displayed Data: Spectrogram/Values, Chromaticity Values, Color Difference Values/Graph, Pass/Fail Result, Color Offset

Measurement time: About 2.4 s (simultaneous measurement SCI / SCE about 5 s)

Repeatability	Spectral reflectance:	Φ 25.4mm/SCI Standard deviation within 0.04% (400 nm to 700 nm: within 0.04%)
	Chromaticity value:	Φ 25.4mm/SCI Standard deviation within ΔE^*ab 0.01 (When a white calibration plate is measured 30 times at 5 second intervals after white calibration)
	Spectral Transmittance:	Φ 25.4mm/SCI Standard deviation within 0.05% (400 nm to 700 nm: within 0.04%)
	Chromaticity value:	Φ 25.4mm/SCI Standard deviation within ΔE^*ab 0.02 (When a white calibration plate is measured 30 times at 5 second intervals after white calibration)

Inter-instrument Error: Φ 25.4mm/SCI Within ΔE^*ab 0.12 (Average for 12 BCRA Series II color tiles)

Size: 370X300X200mm

Weight: 9.6kg

Power Supply: DC 24V, 3A Power Adapter

Light Source Device Life: 5 years, more than 3 million times measurements.

Screen: 7" TFT Capacitive Screen-touch Display

Network calibration: Supports Netmetric

Data Port: USB & Bluetooth

Data Storage Capacity: Standard: 5000 Pcs; Sample: 40000 Pcs. (One PCS can include both SCI and SCE)

Language: English & Chinese

Standard Accessory: White and Black Calibration Board, Checking Green Board, Sample Holder, Φ 4mm, Φ 8mm, Φ 15mm, Φ 25.4mm Aperture, Power Adapter, USB Cable, User Guide, PC Software, Culture dish, Micro Aperture (4mm) Transmission Test Fixture Assembly

Optional Accessory: Micro-printers, instrument inverted test fixtures, petri dishes


GUANGDONG THREENH TECHNOLOGY CO., LTD.



Spectrophotometers



Colorimeters



Haze Meters



Gloss Meters



Test Charts



Light Booths

★ CONTACT US

web: www.3nh.com

Email: 3nh@3nh.com

Tel: 0086-020-82880288

Add: 6-8th floors, Building B33, Low Carbon Headquarters Park, Xincheng Road No.400, Zengcheng District, Guangzhou, Guangdong Province, China