



**EASY TO USE, ACCURATE MEASUREMENT**



# HAZE METER



7in color touch screen



Spectral display



Built-in integrating sphere



PC software extension



## YH1102

YH1102 haze meter (dual caliber) can easily implement ASTM D1003 non-compensation method, full light transmittance, and haze test.

The open sample chamber can be tested vertically and horizontally, which is suitable for more samples to be tested. YH1102 haze meter

adopts PD array detector to meet CIE  $V(\lambda)$  2 degree visual response. Compensation method measurement can achieve high-precision and repeatable light transmittance and haze data measurement.

## PRODUCT FEATURES

### Advantages of haze meter

<b>1</b> Compliant with standard ASTM	Meet a variety of test requirements, Standards compliant: ASTM D1003/1044, GB/T 2410, JJF 1303-2011, CIE 15.2, JIS K7105, JIS K7361, JIS K7136
<b>2</b> Simple operation and quick measurement	The YH1102 haze meter is equipped with a large-size touch screen for easy operation. With a PD array detector, CIE V( $\lambda$ )2 degree visual response enables high precision and repeatable transmittance and fog measurements. USB data output device for docking with laboratory system.
<b>3</b> Dynamic measurement	Independent light source detector and temperature sensor, constantly monitor light source and environmental change, ensure the reliability of test data.
<b>4</b> Support a variety of samples	Independent light source detector and temperature sensor, constantly monitor light source and environmental change, ensure the reliability of test data.
<b>5</b> Support a variety of samples	It provides powerful software for measuring and analyzing fog and light transmittance, which is suitable for quality monitoring and tabulated management of fog and light transmittance data in various industries. The management of users will be digitized at the PC end, the difference of fog and light transmittance will be compared, and the test report form will be generated to facilitate customer customization and management.

## Application industry

The YH1102 haze meter is widely used in glass processing, plastic processing, film, display processing, packaging industry, liquid chemical analysis, etc.



**Model:** YH1102**Optical Geometry:** Transmission: 0/D (parallel light illumination, diffuse reflection reception)**Standards compliant:** ASTM D1003/1044, GB/T 2410, JJF 1303-2011, CIE 15.2, JIS K7105, JIS K7361, JIS K 7136**Integrating Sphere Size:**  $\phi$  154mm**Illuminant:** 400-700nm LED light source**Spectrophotometric Mode:** /**Sensor:** PD array detector, meeting CIE V( $\lambda$ ) 2 degree visual response**Wavelength Range:** /**Wavelength Pitch:** /**Semiband Width:** /**Transmittance range:** 0-100%**Measuring Aperture:**  $\phi$  20mm/ $\phi$  8mm double caliber**Sample size:** The thickness is less than 170mm**Color Space:** /**Color Difference Formula:** /**Other Colorimetric Data:** Haze (ASTM, ISO), transmittance T (ASTM)**Observer Angle:** 2°**Illuminants:** D65, A, C**Displayed Data:** Pass/fail result**Measuring Time:** about 1.5s**Precision:** 0.01**Repeatability:**  $\phi$  20mm Caliber, < 0.05

(After the instrument is warmed up and corrected, the standard deviation value of the standard haze sheet with a haze of about 30 is tested at an interval of 5s)

**Inter-instrument Error:**  $\phi$  20mm Caliber, < 0.4

(After the instrument is warmed up and corrected, test the standard deviation of the haze standard haze sheet and the reference value at an interval of 5s)

**Size:** Length X Width X Height=290X211X511mm**Weight:** About 7.6kg**Power Supply:** DC 24V, 3A Power Adapter**Light Source Device Life:** 5 years, more than 3 million times measurements.**Display:** 7" TFT Capacitive Screen-touch Display**Data Port:** USB & Print serial port**Data Storage:** Standard 1000 Pcs, Sample 20000 Pcs**Language:** Simplified Chinese, Traditional Chinese, English**Working Environment:** Temperature: 0~40°C; Humidity: 0~85% (No Condensation)**Storage Environment:** Temperature: -20~50°C; Humidity: 0~85% (No Condensation)**Standard Accessory:** Power adapter, manual, quality management software (download from official website), data cable, 0% calibration box, measuring caliber**Optional Accessory:** Micro printer, test fixture, standard haze film, foot switch**Notes:** The specifications are subject to change without notice.

## GUANGDONG THREENH TECHNOLOGY CO., LTD.



Spectrophotometers




Colorimeters



Haze Meters



Gloss Meters



Test Charts



Light Booths

## ★ CONTACT US

 web: [www.3nh.com](http://www.3nh.com) Email: [3nh@3nh.com](mailto:3nh@3nh.com)

Tel: 0086-020-82880288

Add: 6-8th floors, Building B33, Low Carbon Headquarters Park, Xincheng Road No.400, Zengcheng District, Guangzhou, Guangdong Province, China